



**VITRINA CALIENTE
HOT SHOWCASE**



FICHA TÉCNICA			
WHF-150L			
Classification Tipo de producto	Heated Countertop Displaycases	Cooling Method <i>Tipo de refrigeración</i>	
Material Material	AISI 201	Defrost Method <i>Descongelar</i>	
Temperature (°C) Temperatura	30 ~ 90	Refrigerant <i>Gas refrigerante</i>	
Climate temperature Temperatura ambiente	25°C RH60%	Refrigerant Amount (g) <i>Cantidad de Gas</i>	
Gross Volume (L) Capacidad bruta	150	Climate type Clase climática	3
Net Volume (L) Capacidad neta		Exterior Dimensions (body) (mm) <i>Dimensiones del cuerpo de la máquina</i>	700×570×678
Shelf QTY <i>Rejillas suministradas</i>	3	Height with Leg and upstand approx.(mm) <i>Altura incluyendo pies ajustables y tope aprox.</i>	678
Shelf Dimensions (mm) <i>Tamaño de rejilla</i>	650x338	Height with Castor (mm) <i>Altura incluyendo ruedas</i>	
Loading capacity per shelf (kg) <i>Carga máxima por rejilla</i>	7	Interior Dimensions (mm) <i>Dimensiones internas</i>	
Tempered glass thickness (mm) Espesor cristal templado (mm)	6	Wood Packing Dimensions (mm) <i>Dimensiones del embalaje</i>	784×641×790
LED temperature <i>Temperatura LED</i>	4000k	Net Weight (kg) <i>Peso neto</i>	49
LED power (W) <i>Potencia luz LED (W)</i>	5 kW	Gross Weight (kg) <i>Peso bruto</i>	70
Power (W) Potencia	1250	Voltage (V/Hz/Ph) <i>Voltaje nominal</i>	220-240/50/1
Power consumption (kWh/24h) <i>Consumo</i>		Auxiliary Heater (W) <i>Calentador auxiliar</i>	
Annual energy consumption (kWh/annum) <i>Consumo annual</i>		Energy efficiency class <i>Clase energética</i>	
Rated Current (A) <i>Corriente nominal</i>	5.7	Thermostat <i>Modelo de termostato</i>	
Integrated humidification system Sistema humidificación integrado	SI	Compressor Model <i>Modelo de compresor</i>	

